

## Black Label Zero FSC®

# Product Description

Black Label Zero enables achieving  ${\rm CO_2}$  net-zero goals. Ideal for black-and-white as well as spot colour applications. The filler and raw materials, production speed and dehydration are carefully monitored to give ideal stiffness and calliper, plus outstanding homogeneity for high-speed copying and printing.

#### **Properties**

Grammage	75	80
[g/m <sup>2</sup> ]		
ISO 536		
Thickness	105	107
[µm]		
ISO 534		
Bulk	1.40	1.34
[cm <sup>3</sup> /g]		
ISO 534		
Whiteness	161	161
CIE		
ISO 11475		
Opacity	92	93
[%]		
ISO 2471		
Brightness	108	108
D65		
ISO 2470-2		

Features

Black Label Zero has been developed for a wide range of applications, including house style, letter paper, reports, memos and presentations. Black Label Zero is the perfect paper supporting your net-zero goals

Size

This media is available in the following size(s) and grain direction

- A4 [210×297 mm] with Long Grain
- A3 [297×420 mm] with Short Grain

Storage

Temperature 10 - 30 °C, Relative Humidity 20 - 70% Repack opened reams or boxes when not in use.

Print

Acclimatize paper 24 hours before printing in print room conditions

(preferably next to printer)

Best results are obtained between 15-25 °C and 30-65% RH (relative

humidity)

Environment,

No Material Safety Data Sheet required.

**Health & Safety** 

ISO 9001 and 14001 certified production site.

ECF (Elemental Chlorine Free) bleaching technique for wood pulp.

Paper waste is suitable for recycling in most countries. Please refer to

local paper recycle station.

### Environmental Certification













#### Disclaimer

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

This document was last edited on: Tuesday, March 18, 2025

Canon Inc.

canon.com

Canon Europe

canon-europe.com

English edition